

CLUSTER™

TYPE:

Ceiling/Wall

PROJECT NAME:

_____ - _____ - _____ - _____ - _____ - 120V

MODEL # SHADE COLOR FIXTURE HEIGHT HALO LED VOLTAGE



SHADE OPTIONS



ST = STANDARD GBU - 2



MODEL - CLUSTER PL 11


LIGHT SOURCE OPTIONS

H = HALOGEN - 11 x 10W 12V G4

or

L = LED - 11 x 1.5W 12V 2700K WW

100 Lumens each LED 30,000 hours



35cm
(13.8")

50cm
(19.7")

DIMMING NOTE:

HALOGEN VERSION - Dimmable with a Low-Voltage Electronic dimmer.

LED VERSION - Dimmable with a leading edge or trailing edge TRIAC dimmer.

SPECIFICATION SHEET

HARCOLOOR DESIGN

HARCOLOOR DESIGN

CLUSTER™

TYPE:

Ceiling

PROJECT NAME:

MODEL #	SHADE COLOR	FIXTURE HEIGHT	HALO	LED	VOLTAGE
					120V



SHADE OPTIONS

ST = STANDARD GBU - 2



MODEL - CLUSTER WL/PL 4


LIGHT SOURCE OPTIONS

H = HALOGEN - 4 x 10W 12V G4

or

L = LED - 4 x 1.5W 12V 2700K WW

100 Lumens each LED 30,000 hours



MODEL - CLUSTER WL/PL 6


LIGHT SOURCE OPTIONS

H = HALOGEN - 6 x 10W 12V G4

or

L = LED - 6 x 1.5W 12V 2700K WW

100 Lumens each LED 30,000 hours



SPECIFICATION SHEET



DIMMING NOTE:

HALOGEN VERSION - Dimmable with a Low-Voltage Electronic dimmer.

LED VERSION - Dimmable with a leading edge or trailing edge TRIAC dimmer.