

BARET™

TYPE:

Wall/Ceiling

PROJECT NAME:

MODEL # - SHADE COLOR - FIXTURE HEIGHT - HALO - LED - VOLTAGE

120V



SHADE OPTIONS

STANDARD ALUMINUM



MODEL - BARET PL/WL 25


LIGHT SOURCE OPTIONS

H = HALOGEN - 3 x 20W 12V G4

or

L = LED - 3 x 1.5W 12V 2700K WW

100 Lumens each LED 30,000 hours



MODEL - BARET PL/WL 35


LIGHT SOURCE OPTIONS

H = HALOGEN - 5 x 10W 12V G4

or

L = LED - 3 x 1.5W 12V 2700K WW

100 Lumens each LED 30,000 hours



SPECIFICATION SHEET

HARCOLOOR DESIGN

DIMMING NOTE:

HALOGEN VERSION - Dimmable with a Low-Voltage Electronic dimmer.

LED VERSION - Dimmable with a leading edge or trailing edge TRIAC dimmer.

A SCANGIFT® BRAND

WWW.HARCOLOORLIGHTING.COM

BARET™

TYPE:

Wall/Ceiling

PROJECT NAME:

120V

MODEL #

SHADE COLOR

FIXTURE HEIGHT

HALO


LED

VOLTAGE



SHADE OPTIONS

STANDARD ALUMINUM



MODEL - BARET PL/WL 50


LIGHT SOURCE OPTIONS

H = HALOGEN - 7 x 10W 12V G4

or

L = LED - 3 x 1.5W 12V 2700K WW

100 Lumens each LED 30,000 hours



MODEL - BARET PL/WL 60


LIGHT SOURCE OPTIONS

H = HALOGEN - 9 x 10W 12V G4

or

L = LED - 3 x 1.5W 12V 2700K WW

100 Lumens each LED 30,000 hours



MODEL - BARET PL/WL 70


LIGHT SOURCE OPTIONS

H = HALOGEN - 12 x 10W 12V G4

or

L = LED - 3 x 1.5W 12V 2700K WW

100 Lumens each LED 30,000 hours



MODEL - BARET PL/WL 80

LIGHT SOURCE OPTIONS

H = HALOGEN - 12 x 10W 12V G4

or

L = LED - 3 x 1.5W 12V 2700K WW

100 Lumens each LED 30,000 hours

SPECIFICATION SHEET

HARCOLOOR
DESIGN

DIMMING NOTE:

HALOGEN VERSION - Dimmable with a Low-Voltage Electronic dimmer.

LED VERSION - Dimmable with a leading edge or trailing edge TRIAC dimmer.

A SCANGIFT® BRAND

WWW.HARCOLOORLIGHTING.COM

BARET™

TYPE:

Wall/Ceiling

PROJECT NAME:

120V

MODEL #

SHADE COLOR

FIXTURE HEIGHT

HALO

LED

VOLTAGE



SHADE OPTIONS

STANDARD ALUMINUM

MODEL - BARET PL/WL 100


LIGHT SOURCE OPTIONS

H = HALOGEN - 15 x 10W 12V G4

or

L = LED - 3 x 1.5W 12V 2700K WW

100 Lumens each LED 30,000 hours



MODEL - BARET PL/WL 125


LIGHT SOURCE OPTIONS

H = HALOGEN - 20 x 10W 12V G4

or

L = LED - 3 x 1.5W 12V 2700K WW

100 Lumens each LED 30,000 hours



MODEL - BARET PL/WL 150


LIGHT SOURCE OPTIONS

H = HALOGEN - 20 x 10W 12V G4

or

L = LED - 3 x 1.5W 12V 2700K WW

100 Lumens each LED 30,000 hours



MODEL - BARET PL/WL 250


LIGHT SOURCE OPTIONS

H = HALOGEN - 20 x 10W 12V G4

or

L = LED - 3 x 1.5W 12V 2700K WW

100 Lumens each LED 30,000 hours



SPECIFICATION SHEET

HARCOLOOR
DESIGN

DIMMING NOTE:

HALOGEN VERSION - Dimmable with a Low-Voltage Electronic dimmer.

LED VERSION - Dimmable with a leading edge or trailing edge TRIAC dimmer.

A SCANGIFT® BRAND

WWW.HARCOLOORLIGHTING.COM