

BUBBLES™ OVAL

TYPE:

Suspensions

PROJECT NAME: _____

MODEL # _____ SHADE COLOR _____ FIXTURE HEIGHT _____ HALO _____ LED _____ VOLTAGE 120V

SHADE OPTIONS

ST = STANDARD GBU - 2




MODEL - BUBBLES OVAL HL 12

LIGHT SOURCE OPTIONS

H = HALOGEN - 12 x 10W 12V G4
 or
 L = LED - 12 x 1.5W 12V 2700K WW
 100 Lumens each LED 30,000 hours

FIXTURE HEIGHT OPTIONS (A)

32 = 32"
 44 = 44"
 56 = 56"
 CH = Custom height available. Please contact our office.
 NOTE 1: Suspension Rod is not field cuttable.
 NOTE 2: Height stated above may vary + - 1" - 4" due to the fixture arms can be adjusted slightly as the fixture is hand made and organic in shape.



SPECIFICATION SHEET

HARCOLOOR DESIGN

DIMMING NOTE:

HALOGEN VERSION - Dimmable with a Low-Voltage Electronic dimmer.
 LED VERSION - Dimmable with a leading edge or trailing edge TRIAC dimmer.

BUBBLES™ OVAL

TYPE:

Suspensions

PROJECT NAME:

MODEL #	SHADE COLOR	FIXTURE HEIGHT	HALO	LED	VOLTAGE
					120V




SHADE OPTIONS

ST = STANDARD GBU - 2



MODEL - BUBBLES OVAL HL 15

BUBBLES OVAL



160cm x 70cm
(63"L x 27.6"W)

LIGHT SOURCE OPTIONS

H = HALOGEN - 15 x 10W 12V G4
or
L = LED - 15 x 1.5W 12V 2700K WW
100 Lumens each LED 30,000 hours

FIXTURE HEIGHT OPTIONS (A)

32 = 32"
44 = 44"
56 = 56"

CH = Custom height available. Please contact our office.
NOTE 1: Suspension Rod is not field cuttable.
NOTE 2: Height stated above may vary + - 1" - 4" due to the fixture arms can be adjusted slightly as the fixture is hand made and organic in shape.

SPECIFICATION SHEET



DIMMING NOTE:

HALOGEN VERSION - Dimmable with a Low-Voltage Electronic dimmer.
LED VERSION - Dimmable with a leading edge or trailing edge TRIAC dimmer.