BUBBLESTM

TYPE:

Suspension

PROJECT NAME:


120V

FIXTURE HEIGHT VOLTAGE SHADE COLOR MODEL #

SHADE OPTIONS

ST = STANDARD GBU - 2





SPECIFICATION SHEET

MODEL - BUBBLES HL 7

LIGHT SOURCE OPTIONS

 $H = HALOGEN - 7 \times 10W 12V G4$

 $L = LED - 7 \times 1.5W 12V 2700K WW$

100 Lumens each LED 30,000 hours

FIXTURE HEIGHT OPTIONS (A)

32 = 32''

44 = 44''

56 = 56"

CH = Custom height available. Please contact our office.

NOTE 1: Suspension Rod is not field cuttable.

NOTE 2: Height stated above may vary + - 1" - 4" due to the fixture arms can be adjusted slightly as the fixture

is hand made and organic in shape.

DIMMING NOTE:

HALOGEN VERSION - Dimmable with a Low-Voltage Electronic dimmer. LED VERSION - Dimmable with a leading edge or trailing edge TRIAC dimmer.


Suspension

PROJECT NAME:

				-	_	120V
MODEL #	SHADE COLOR	FIXTURE HEIGHT	HALO	LED		VOLTAGE

SHADE OPTIONS

ST = STANDARD GBU - 2




MODEL - BUBBLES HL 9

LIGHT SOURCE OPTIONS	FIXTURE HEIGHT OPTIONS (A)		
H = HALOGEN - 9 x 10W 12V G4	32 = 32"		
or	44 = 44''		
I = IED 0 × 1 5\\\/ 12\\/ 2700K \\/\\\/	56 - 56"		

NOTE 1: Suspension Rod is not field cuttable. NOTE 2: Height stated above may vary + - 1" - 4" due to the fixture arms can be adjusted slightly as the fixture is hand made and organic in shape.

CH = Custom height available. Please contact our office.




MODEL - BUBBLES HL 12

100 Lumens each LED 30,000 hours

LIGHT SOURCE OPTIONS	FIXTURE HEIGHT OPTIONS (A)		
H = HALOGEN - 12 x 10W 12V G4	32 = 32"		
or	44 = 44"		
L = LED - 12 x 1.5W 12V 2700K WW	56 = 56"		
100 Lumens each LED 30,000 hours	CH = Custom height gygilable. I		

Custom height available. Please contact our office. NOTE 1: Suspension Rod is not field cuttable.

NOTE 2: Height stated above may vary + - 1" - 4" due to the fixture arms can be adjusted slightly as the fixture is hand made and organic in shape.



SPECIFICATION SHEET

MODEL - BUBBLES HL 15

LIGHT SOURCE OPTIONS	FIXTURE HEIGHT OPTIONS (A)			
H = HALOGEN - 15 x 10W 12V G4	32 = 32"			
or	44 = 44"			
L = LED - 15 x 1.5W 12V 2700K WW	56 = 56"			

100 Lumens each LED 30,000 hours CH = Custom height available. Please contact our office. NOTE 1: Suspension Rod is not field cuttable.

> NOTE 2: Height stated above may vary + - 1" - 4" due to the fixture arms can be adjusted slightly as the fixture is hand made and organic in shape.

DIMMING NOTE:

HALOGEN VERSION - Dimmable with a Low-Voltage Electronic dimmer. LED VERSION - Dimmable with a leading edge or trailing edge TRIAC dimmer.

BUBBLESTM

TYPE:

Suspension


PROJECT NAME:

MODEL# SHADE COLOR FIXTURE HEIGHT HALO LED VOLTAGE

SHADE OPTIONS

ST = STANDARD GBU - 2





MODEL - BUBBLES HL 20


LIGHT SOURCE OPTIONS	FIXTURE HEIGHT OPTIONS (A)		
H = HALOGEN - 20 x 10W 12V G4	32 = 32"		
or	44 = 44"		

56 = 56"

or L = LED - 14 x 1.5W 12V 2700K WW 100 Lumens each LED 30,000 hours

CH = Custom height available. Please contact our office. NOTE 1: Suspension Rod is not field cuttable.

NOTE 2: Height stated above may vary + - 1" - 4" due to the fixture arms can be adjusted slightly as the fixture is hand made and organic in shape.



MODEL - BUBBLES HL 30


LIGHT SOURCE OPTIONS H = HALOGEN - 30 x 5W 12V G4 or FIXTURE HEIGHT OPTIONS (A) 32 = 32" 44 = 44"

L = LED - 20 x 1.5W 12V 2700K WW 56 = 56"

100 Lumens each LED 30,000 hours CH = Custom height available. Please contact our office.

NOTE 1: Suspension Rod is not field cuttable.

NOTE 2: Height stated above may vary + - 1" - 4" due to the fixture arms can be adjusted slightly as the fixture is hand made and organic in shape.



DESIGN

HARCOLOOR

HARCOLOOR

MODEL - BUBBLES HL 40

LIGHT SOURCE OPTIONS FIXTURE HEIGHT OPTIONS (A)

H = HALOGEN - 40 x 5W 12V G4 32 = 32" or 44 = 44" L = LED - 40 x 1.5W 12V 2700K WW 56 = 56"

100 Lumens each LED 30,000 hours CH = Custom height available. Please contact our office.

NOTE 1: Suspension Rod is not field cuttable.

NOTE 2: Height stated above may vary + - 1" - 4" due to the fixture arms can be adjusted slightly as the fixture is hand made and organic in shape.

DIMMING NOTE:

 $\label{thm:logen} \mbox{HALOGEN VERSION - Dimmable with a Low-Voltage Electronic dimmer.} \\ \mbox{LED VERSION - Dimmable with a leading edge or trailing edge TRIAC dimmer.} \\$

DESIGN

BUBBLESTM

TYPE:

Suspension


PROJECT NAME:

120V

FIXTURE HEIGHT SHADE COLOR VOLTAGE MODEL #

SHADE OPTIONS

ST = STANDARD GBU - 2



MODEL - BUBBLES HL 50

LIGHT SOURCE OPTIONS

 $H = HALOGEN - 50 \times 5W 12V G4$

 $L = LED - 50 \times 1.5W 12V 2700K WW$ 100 Lumens each LED 30,000 hours

FIXTURE HEIGHT OPTIONS (A)

32 = 32''

44 = 44''

56 = 56"

CH = Custom height available. Please contact our office.

NOTE 1: Suspension Rod is not field cuttable.

NOTE 2: Height stated above may vary + - 1" - 4" due to the fixture arms can be adjusted slightly as the fixture

is hand made and organic in shape.

SPECIFICATION SHEET **HARCOLOOR** HARCOLOOR DESIGNATION OF THE PROPERTY OF THE P

DIMMING NOTE:

HALOGEN VERSION - Dimmable with a Low-Voltage Electronic dimmer. LED VERSION - Dimmable with a leading edge or trailing edge TRIAC dimmer.