

**TYPE:**

Suspension

**PROJECT NAME:**

MODEL #	SHADE COLOR	FIXTURE HEIGHT	HALO	LED	VOLTAGE
					120V



SHADE OPTIONS

ST = STANDARD GFL



MODEL - FLAG OVAL HL 10


LIGHT SOURCE OPTIONS

H = HALOGEN - 10 x 10W 12V G4  
 or  
 L = LED - 10 x 1.5W 12V 2700K WW  
 100 Lumens each LED 30,000 hours

FIXTURE HEIGHT OPTIONS (A)

32 = 32"  
 44 = 44"  
 56 = 56"  
 CH = Custom height available. Please contact our office.  
 NOTE 1: Suspension Rod is not field cuttable.  
 NOTE 2: Height stated above may vary + - 1" - 4" due to the fixture arms can be adjusted slightly as the fixture is hand made and organic in shape.

SPECIFICATION SHEET



HARCOLOOR DESIGN

DIMMING NOTE:


HALOGEN VERSION - Dimmable with a Low-Voltage Electronic dimmer.  
 LED VERSION - Dimmable with a leading edge or trailing edge TRIAC dimmer.

MODEL #	SHADE COLOR	FIXTURE HEIGHT	HALO	LED	VOLTAGE
					120V



**SHADE OPTIONS**

ST = STANDARD GFL




**MODEL - FLAG OVAL HL 14**

**LIGHT SOURCE OPTIONS**

H = HALOGEN - 14 x 10W 12V G4  
or  
L = LED - 14 x 1.5W 12V 2700K WW  
100 Lumens each LED 30,000 hours

**FIXTURE HEIGHT OPTIONS (A)**

32 = 32"  
44 = 44"  
56 = 56"  
CH = Custom height available. Please contact our office.  
NOTE 1: Suspension Rod is not field cuttable.  
NOTE 2: Height stated above may vary + - 1" - 4" due to the fixture arms can be adjusted slightly as the fixture is hand made and organic in shape.




**MODEL - FLAG OVAL HL 20**

**LIGHT SOURCE OPTIONS**

H = HALOGEN - 20 x 10W 12V G4  
or  
L = LED - 20 x 1.5W 12V 2700K WW  
100 Lumens each LED 30,000 hours

**FIXTURE HEIGHT OPTIONS (A)**

32 = 32"  
44 = 44"  
56 = 56"  
CH = Custom height available. Please contact our office.  
NOTE 1: Suspension Rod is not field cuttable.  
NOTE 2: Height stated above may vary + - 1" - 4" due to the fixture arms can be adjusted slightly as the fixture is hand made and organic in shape.



**MODEL - FLAG OVAL HL 24**

**LIGHT SOURCE OPTIONS**

H = HALOGEN - 24 x 10W 12V G4  
or  
L = LED - 24 x 1.5W 12V 2700K WW  
100 Lumens each LED 30,000 hours

**FIXTURE HEIGHT OPTIONS (A)**

32 = 32"  
44 = 44"  
56 = 56"  
CH = Custom height available. Please contact our office.  
NOTE 1: Suspension Rod is not field cuttable.  
NOTE 2: Height stated above may vary + - 1" - 4" due to the fixture arms can be adjusted slightly as the fixture is hand made and organic in shape.

**DIMMING NOTE:**

HALOGEN VERSION - Dimmable with a Low-Voltage Electronic dimmer.  
LED VERSION - Dimmable with a leading edge or trailing edge TRIAC dimmer.

SPECIFICATION SHEET


HARCOLOOR DESIGN

MODEL #	SHADE COLOR	FIXTURE HEIGHT	HALO	LED	VOLTAGE
					120V



**SHADE OPTIONS**

ST = STANDARD GFL



MODEL - FLAG OVAL HL 30


LIGHT SOURCE OPTIONS

H = HALOGEN - 30 x 5W 12V G4  
or  
L = LED - 30 x 1.5W 12V 2700K WW  
100 Lumens each LED 30,000 hours

FIXTURE HEIGHT OPTIONS (A)

32 = 32"  
44 = 44"  
56 = 56"

CH = Custom height available. Please contact our office.  
NOTE 1: Suspension Rod is not field cuttable.  
NOTE 2: Height stated above may vary + - 1" - 4" due to the fixture arms can be adjusted slightly as the fixture is hand made and organic in shape.



MODEL - FLAG OVAL HL 35

LIGHT SOURCE OPTIONS

H = HALOGEN - 35 x 5W 12V G4  
or  
L = LED - 35 x 1.5W 12V 2700K WW  
100 Lumens each LED 30,000 hours

FIXTURE HEIGHT OPTIONS (A)

32 = 32"  
44 = 44"  
56 = 56"

CH = Custom height available. Please contact our office.  
NOTE 1: Suspension Rod is not field cuttable.  
NOTE 2: Height stated above may vary + - 1" - 4" due to the fixture arms can be adjusted slightly as the fixture is hand made and organic in shape.

SPECIFICATION SHEET



DIMMING NOTE:

HALOGEN VERSION - Dimmable with a Low-Voltage Electronic dimmer.  
LED VERSION - Dimmable with a leading edge or trailing edge TRIAC dimmer.