

# REFLEXION™

TYPE:

Wall/Ceiling

PROJECT NAME:

MODEL #	SHADE COLOR	FIXTURE HEIGHT	HALO	LED	VOLTAGE
					120V



### SHADE OPTIONS

ST = STANDARD ALUMINUM



— 40cm —  
(15.7")

25cm  
(9.8")

MODEL - REFLEXION WL/PL 3

### LIGHT SOURCE OPTIONS

H = HALOGEN - 3 x 20W 12V G4

or

L = LED - 3 x 1.5W 12V 2700K WW

100 Lumens each LED 30,000 hours



— 50cm —  
(19.7")

30cm  
(11.8")

MODEL - REFLEXION WL/PL 5

### LIGHT SOURCE OPTIONS

H = HALOGEN - 5 x 10W 12V G4

or

L = LED - 5 x 1.5W 12V 2700K WW

100 Lumens each LED 30,000 hours

### DIMMING NOTE:

HALOGEN VERSION - Dimmable with a Low-Voltage Electronic dimmer.

LED VERSION - Dimmable with a leading edge or trailing edge TRIAC dimmer.

SPECIFICATION SHEET

HARCOLOOR DESIGN

A SCANGIFT® BRAND

WWW.HARCOLOORLIGHTING.COM

# REFLEXION™

TYPE:

Wall/Ceiling


PROJECT NAME:

MODEL #	SHADE COLOR	FIXTURE HEIGHT	HALO	LED	VOLTAGE
					120V



### SHADE OPTIONS

ST = STANDARD ALUMINUM



MODEL - REFLEXION WL/PL 7


### LIGHT SOURCE OPTIONS

H = HALOGEN - 7 x 10W 12V G4

or

L = LED - 7 x 1.5W 12V 2700K WW

100 Lumens each LED 30,000 hours



MODEL - REFLEXION WL/PL 9


### LIGHT SOURCE OPTIONS

H = HALOGEN - 9 x 10W 12V G4

or

L = LED - 9 x 1.5W 12V 2700K WW

100 Lumens each LED 30,000 hours



MODEL - REFLEXION WL/PL 12

### LIGHT SOURCE OPTIONS

H = HALOGEN - 12 x 10W 12V G4

or

L = LED - 12 x 1.5W 12V 2700K WW

100 Lumens each LED 30,000 hours

SPECIFICATION SHEET



### DIMMING NOTE:

HALOGEN VERSION - Dimmable with a Low-Voltage Electronic dimmer.

LED VERSION - Dimmable with a leading edge or trailing edge TRIAC dimmer.