

SOLANGE™

TYPE:

Suspension

PROJECT NAME:

_____ - _____ - _____ - _____ - _____ - 120V

MODEL #

SHADE COLOR

FIXTURE HEIGHT

HALO

LED

VOLTAGE


SHADE OPTIONS



ST = STANDARD MULTICOLOR



SPECIFICATION SHEET



60cm
(23.6")

A

MODEL - SOLANGE HL 9

LIGHT SOURCE OPTIONS

H = HALOGEN - 9 x 10W 12V G4
or
L = LED - 9 x 1.5W 12V 2700K WW
100 Lumens each LED 30,000 hours

FIXTURE HEIGHT OPTIONS (A)

32 = 32"
44 = 44"
56 = 56"

CH = Custom height available. Please contact our office.

NOTE 1: Suspension Rod is not field cuttable.

NOTE 2: Height stated above may vary + .1" - .4" due to the fixture arms can be adjusted slightly as the fixture is hand made and organic in shape.

DIMMING NOTE:

HALOGEN VERSION - Dimmable with a Low-Voltage Electronic dimmer.

LED VERSION - Dimmable with a leading edge or trailing edge TRIAC dimmer.

HARCOLOOR DESIGN

SOLANGE™

TYPE:

Suspension

PROJECT NAME:

MODEL # SHADE COLOR FIXTURE HEIGHT HALO LED VOLTAGE


120V



SHADE OPTIONS



ST = STANDARD MULTICOLOR



65cm
(25.6")

A

MODEL - SOLANGE HL 12

LIGHT SOURCE OPTIONS

H = HALOGEN - 12 x 10W 12V G4
or
L = LED - 12 x 1.5W 12V 2700K WW
100 Lumens each LED 30,000 hours


FIXTURE HEIGHT OPTIONS (A)

32 = 32"
44 = 44"
56 = 56"

CH = Custom height available. Please contact our office.

NOTE 1: Suspension Rod is not field cuttable.

NOTE 2: Height stated above may vary + - 1" - 4" due to the fixture arms can be adjusted slightly as the fixture is hand made and organic in shape.



75cm
(29.5")

A

MODEL - SOLANGE HL 15

LIGHT SOURCE OPTIONS

H = HALOGEN - 15 x 10W 12V G4
or
L = LED - 15 x 1.5W 12V 2700K WW
100 Lumens each LED 30,000 hours

FIXTURE HEIGHT OPTIONS (A)

32 = 32"
44 = 44"
56 = 56"

CH = Custom height available. Please contact our office.

NOTE 1: Suspension Rod is not field cuttable.

NOTE 2: Height stated above may vary + - 1" - 4" due to the fixture arms can be adjusted slightly as the fixture is hand made and organic in shape.

SPECIFICATION SHEET

HARCOOLOR DESIGN

DIMMING NOTE:

HALOGEN VERSION - Dimmable with a Low-Voltage Electronic dimmer.

LED VERSION - Dimmable with a leading edge or trailing edge TRIAC dimmer.