

STRAWBERRY™

TYPE:

Ceiling/Wall

PROJECT NAME:

										120V	
MODEL #	SHADE COLOR		FIXTURE HEIGHT		HALO	LED	VOLTAGE				
SHADE OPTIONS	 2	 4	 5	 7	 8	 9	 10	 15			
ST = STANDARD GSW MULTICOLOR											



STRAWBERRY

MODEL - STRAWBERRY WL/PL 1

LIGHT SOURCE OPTIONS

H = HALOGEN - 1 x 20W 12V G4

or

L = LED - 1 x 1.5W 12V 2700K WW



100 Lumens each LED 30,000 hours

DIMMING NOTE:

HALOGEN VERSION - Dimmable with a Low-Voltage Electronic dimmer.

LED VERSION - Dimmable with a leading edge or trailing edge TRIAC dimmer.

SPECIFICATION SHEET



HARCOLOOR
DESIGN



HARCOLOOR
DESIGN

STRAWBERRY™


TYPE:

Ceiling/Wall

PROJECT NAME:

MODEL #	SHADE COLOR	FIXTURE HEIGHT	HALO	LED	VOLTAGE
SHADE OPTIONS					120V
ST = STANDARD GSW MULTICOLOR					

STRAWBERRY



MODEL - STRAWBERRY WL/PL 3

LIGHT SOURCE OPTIONS


H = HALOGEN - 3 x 20W 12V G4

or

L = LED - 3 x 1.5W 12V 2700K WW

100 Lumens each LED 30,000 hours

STRAWBERRY



MODEL - STRAWBERRY WL/PL 5

LIGHT SOURCE OPTIONS

H = HALOGEN - 5 x 10W 12V G4

or

L = LED - 5 x 1.5W 12V 2700K WW

100 Lumens each LED 30,000 hours

SPECIFICATION SHEET



DIMMING NOTE:

HALOGEN VERSION - Dimmable with a Low-Voltage Electronic dimmer.

LED VERSION - Dimmable with a leading edge or trailing edge TRIAC dimmer.