

TARGET™

TYPE:

Wall/Ceiling

PROJECT NAME:

_____ - _____ - _____ - _____ - _____ - 120V

MODEL # SHADE COLOR FIXTURE HEIGHT HALO LED VOLTAGE



SHADE OPTIONS

ST = STANDARD ALUMINUM FLEXIBLE



MODEL - TARGET WL/PL 1


LIGHT SOURCE OPTIONS

H = HALOGEN - 1 x 35W 12V G4

or

L = LED - 1 x 1.5W 12V 2700K WW

100 Lumens each LED 30,000 hours



SPECIFICATION SHEET

HARCOOLOR DESIGN

HARCOOLOR DESIGN

DIMMING NOTE:

HALOGEN VERSION - Dimmable with a Low-Voltage Electronic dimmer.

LED VERSION - Dimmable with a leading edge or trailing edge TRIAC dimmer.

Wall/Ceiling


PROJECT NAME:

MODEL #	SHADE COLOR	FIXTURE HEIGHT	HALO	LED	VOLTAGE
					120V



SHADE OPTIONS


ST = STANDARD ALUMINUM FLEXIBLE



MODEL - TARGET WL/PL 2

LIGHT SOURCE OPTIONS


H = HALOGEN - 2 x 35W 12V G4
or
L = LED - 2 x 1.5W 12V 2700K WW
100 Lumens each LED 30,000 hours



MODEL - TARGET WL/PL 3

LIGHT SOURCE OPTIONS

H = HALOGEN - 3 x 35W 12V G4
or
L = LED - 3 x 1.5W 12V 2700K WW
100 Lumens each LED 30,000 hours



MODEL - TARGET WL/PL 5

LIGHT SOURCE OPTIONS

H = HALOGEN - 5 x 35W 12V G4
or
L = LED - 5 x 1.5W 12V 2700K WW
100 Lumens each LED 30,000 hours

SPECIFICATION SHEET



DIMMING NOTE:

HALOGEN VERSION - Dimmable with a Low-Voltage Electronic dimmer.
LED VERSION - Dimmable with a leading edge or trailing edge TRIAC dimmer.